IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1. (Currently Amended) Device-A device for recording information in blocks having logical addresses on a record carrier, which device comprises the device comprising:
- [[-]] recording means (22) for recording marks in a track on the record carrier representing the information, and
- [[-]] control means (20) for controlling the recording by locating each block at a physical address in the track, the control means comprising:
- [[-]] addressing means (31) for translating the logical addresses into the physical addresses and vice versa in dependence of defect management information,
 - [[-]] defect management means (32) for detecting defects and

Amendment in Reply to Office Action of February 13, 2008

maintaining the defect management information, the defect
management information including assignment information indicative
of assignment of physical addresses in first parts of the track to
at least one user data area, assignment of physical addresses in
second parts of the track to defect management areas and assignment
of the defect management information to the defect management
areas, and the defect management information including remapping
information indicative for translating a logical address initially
mapped to a physical address exhibiting a defect to an alternate
physical address in a defect management area,

- [[-]] data type detection means (33)—for detecting a data type of recorded information, in particular the type being including a streaming type for real-time data—like digitally encoded video, or non-streaming type for random data—like—computer data—files, and
- [[-]] defect management area reassignment means (34) for dynamically changing said assignment information in dependence of the data type recorded on the record carrier.
 - 2. (Currently Amended) Device The device as claimed in claim

- 1, wherein the defect management area reassignment means (34)—are for changing said assignment information from a distributed layout having the first parts and the second parts of the track alternatingly arranged to a contiguous layout having a substantially uninterrupted user data area in dependence of the data type being streaming, or vice versa.
- 3.(Currently Amended) Device—The device as claimed in claim 2, wherein the defect management area reassignment means (34)—are for changing said assignment information for a first physical address range to the distributed layout and for a second physical address range to the contiguous layout, the first physical address range containing information of the non-streaming type and the second physical address range containing information of the streaming type.
- 4.(Currently Amended) Device—The device as claimed in claim
 1, wherein the defect management area reassignment means (34) are
 for assigning a defect to a first defect management area for

information of the streaming type, or to a second defect management area for information of the non-streaming type.

- 5.(Currently Amended) Device <u>The device</u> as claimed in claim 4, wherein the defect management area reassignment means (34) are for double assigning by remapping a same defect to both the first defect management area and the second defect management area.
- 6.(Currently Amended) <u>Device—The device</u> as claimed in claim 5, wherein the defect management area reassignment means (34)—are for performing the double assigning as a background process.
- 7.(Currently Amended) Device—The device as claimed in claim
 4, wherein the defect management area reassignment means (34)—are
 changing the assigning of physical address to the first defect
 management area for information of the streaming type, or to the
 second defect management area for information of the non-streaming
 type in dependence of information recorded or defects detected on
 the record carrier.

- 8.(Currently Amended) Device—The device as claimed in claim
 1, wherein the defect management area reassignment means (34)—are
 for, in the event that the translation of logical address to
 physical address of previously recorded blocks is affected by said
 reassignment, moving the previously recorded blocks to a different
 physical address that after the reassignment corresponds to the
 logical address, and/or by adapting file management information by
 amending the logical addresses of the affected of previously
 recoded blocks.
- 9.(Currently Amended) Device—The device as claimed in claim
 1, wherein the data type detection means (33) are for detecting the data type by monitoring commands for recording or retrieving information, by retrieving record carrier information indicative of the data type, by detecting a data type from the data structure of the recorded information, or by detecting file system information, or by communicating with a host device.

- 10.(Currently Amended) Method of defect management for recording of information in blocks having logical addresses on a record carrier by carrier, the method comprising the acts of:
 - [[-]] locating each block at a physical address in the track,
- [[-]] translating the logical addresses into the physical addresses and vice versa in dependence of defect management information,
- [[-]] detecting defects and maintaining the defect management information, the defect management information including assignment information indicative of assignment of physical addresses in first parts of the track to at least one user data area, assignment of physical addresses in second parts of the track to defect management areas and assignment of the defect management information to the defect management areas, and the defect management information including remapping information indicative for translating a logical address initially mapped to a physical address exhibiting a defect to an alternate physical address in a defect management area,

the method comprising

- [[-]] detecting a data type of recorded information, in particular the type being including a streaming type for real-time data like digitally encoded videe, or non-streaming type for random data-like computer data files, and
- [[-]] <u>dynamically</u> changing said assignment information in dependence of the data type <u>recorded</u> on the record carrier.
- 11. (Currently Amended) Computer program product for defect management for recording information, which program is operative A computer readable medium embodying a computer program, the computer program when executed by a processor is configured to cause a the processor to perform the method as claimed in claim 10.
- 12.(New) The method claim 10, wherein the dynamically changing act includes double assigning a same defect to a first defect management area for information of the streaming type, and to a second defect management area for information of the non-streaming type, by remapping the same defect to both the first defect management area and the second defect management area.

13.(New) The method claim 12, wherein the double assigning is performed as a background process.